

Printing date 03/16/2022

Reviewed on 03/14/2022

1 Identification

- · Product name
- · Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran
- Item number: 03-1410
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Strem Chemicals, Inc. 7 Mulliken Way NEWBURYPORT, MA 01950 USA info@strem.com
- · Information department: Technical Department
- Emergency telephone number: EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

\mathbf{V}		
Flam. Liq. 2	H225	Highly flammable liquid and vapor.
Pyr. Liq. 1	H250	Catches fire spontaneously if exposed to air.
Water-react.	<i>H260</i>	In contact with water releases flammable gases, which may ignite spontaneously.
GH	S08 Health ha	izard
Carc. 2	H351	Suspected of causing cancer.
GH	S05 Corrosion	1
Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
GH	'S07	
Acute Tox. 4	H302	Harmful if swallowed.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
· Hazard pictog	ements The pro	oduct is classified and labeled according to the Globally Harmonized System (GHS).
		(Contd. on page 2)

Trade name: CALSELECT[™] Lithium triethylborohydride, 1M in tetrahydrofuran

Printing date 03/16/2022

CHEMICALS, INC.

Reviewed on 03/14/2022

Signal w	ord Danger (Contd. of page
0	letermining components of labeling:
	rofuran [109-99-9]
	iethylhydroborate
triethylbo	
	tatements
H225	Highly flammable liquid and vapor.
H250	Catches fire spontaneously if exposed to air.
H260	In contact with water releases flammable gases, which may ignite spontaneously.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H351	Suspected of causing cancer.
Н335-Н3	36 May cause respiratory irritation. May cause drowsiness or dizziness.
	onary statements
	361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wate shower.
P305+P3	351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P403+P2	
P411+P2	
P422	Store contents under inert gas.
P501	Dispose of contents/container in accordance with local/regional/national/internation
	regulations.
3	$\begin{array}{l} 2 \\ Fire = 4 \\ Reactivity = 2 \end{array}$
The subs	tance demonstrates unusual reactivity with water.
	ntings (scale 0 - 4)
HEALTH	*4 $Health = *4$
FIRE	4 $Fire = 4$
REACTIVI	[2] Reactivity = 2
Other ha	zaras of PBT and vPvB assessment
	t applicable.
1 01.110	
vPvB: No	
vPvB: No	
	sition/information on ingredients
Compos	sition/information on ingredients
Compos Chemica	l characterization: Mixtures
Compos Chemica	
Compos Chemica Descripti	l characterization: Mixtures
Compos Chemica Descripti Dangero	l characterization: Mixtures ion: Mixture of the substances listed below with nonhazardous additions. us components:
Compos Chemica Descripti Dangero 109-99	l characterization: Mixtures ion: Mixture of the substances listed below with nonhazardous additions. us components:

(Contd. of page 2)

5.0%

Safety Data Sheet according to OSHA HCS

Printing date 03/16/2022

Reviewed on 03/14/2022

Trade name: CALSELECT[™] Lithium triethylborohydride, 1M in tetrahydrofuran

97-94-9 triethylborane

4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:
- Immediately call a doctor.
- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. • Environmental precautions: Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). *Use neutralizing agent.* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals · PAC-1: 109-99-9 Tetrahydrofuran [109-99-9] 100 ppm (Contd. on page 4)

Printing date 03/16/2022

CHEMICALS, INC

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

22560-16-3	lithium triethylhydroborate	(Contd. of page 3) <i>1.2 mg/m3</i>
· PAC-2:		
109-99-9	Tetrahydrofuran [109-99-9]	500 ppm
22560-16-3	lithium triethylhydroborate	13 mg/m3
• PAC-3:		
109-99-9	Tetrahydrofuran [109-99-9]	5000* ppm
22560-16-3	lithium triethylhydroborate	79 mg/m3

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

109-99-9 Tetrahydrofuran [109-99-9]

- PEL Long-term value: 590 mg/m³, 200 ppm
- REL Short-term value: 735 mg/m³, 250 ppm
- Long-term value: 590 mg/m³, 200 ppm
- TLV Short-term value: 295 mg/m³, 100 ppm Long-term value: 147 mg/m³, 50 ppm Skin

(Contd. on page 5)

Printing date 03/16/2022

CHEMICALS, INC.

Reviewed on 03/14/2022

Trade name: CALSELECT[™] Lithium triethylborohydride, 1M in tetrahydrofuran

	(Contd. of page
	redients with biological limit values:
	99-9 Tetrahydrofuran [109-99-9]
BEI	2 mg/L
	Medium: urine
	Time: end of shift
4.4.4	Parameter: Tetrahydrofuran itional information: The lists that were valid during the creation were used as basis.
	osure controls
	conal protective equipment: Wear protective clothing eral protective and hygienic measures:
	<i>p</i> away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	id contact with the eyes and skin.
	<i>uthing equipment:</i> A NIOSH approved respirator in accordance with 29 CFR 1910.134.
	ection of hands:
Due chen Sele	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the preparation/ nical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation erial of gloves
vari of th Pen	selection of the suitable gloves does not only depend on the material, but also on further marks of quality a es from manufacturer to manufacturer. As the product is a preparation of several substances, the resistar e glove material can not be calculated in advance and has therefore to be checked prior to the application. etration time of glove material
obse	exact break through time has to be found out by the manufacturer of the protective gloves and has to prved.
Eye	protection:
	Tightly sealed goggles
Phy	vsical and chemical properties
Info	rmation on basic physical and chemical properties

· Information on basic physical and	chemical properties	
• General Information		
· Appearance:		
Form:	Liquid	
Color:	Pale	
· Odor:	Characteristic	
• Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
		(Contd. on page 6)

Printing date 03/16/2022

CHEMICALS, INC.

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

	(Contd. of page
Boiling point/Boiling range:	65.5 °C (150 °F)
Flash point:	-21 °C (-6 °F)
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	230 °C (446 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Spontaneously flammable in air.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	12.0 Vol %
Vapor pressure at 20 °C (68 °F):	200 hPa (150 mm Hg)
Density at 20 °C (68 °F):	0.88571 g/cm ³ (7.39125 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	75.0 %
VOC content:	75.0 %
	664.3 g/l / 5.54 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions Contact with water releases flammable gases.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Printing date 03/16/2022

CHEMICALS. INC

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

(Contd. of page 6)

1 Ta	oxicological information
· In	formation on toxicological effects
·Ac	cute toxicity:
·LL	D/LC50 values that are relevant for classification:
10	9-99-9 Tetrahydrofuran [109-99-9]
Or	al LD50 2500 mg/kg (rat)
97	-94-9 triethylborane
Or	al LD50 235 mg/kg (rat)
· Pr	imary irritant effect:
	the skin: Caustic effect on skin and mucous membranes.
· on	the eye: Strong caustic effect.
	nsitization: No sensitizing effects known.
· Aa	lditional toxicological information:
	e product shows the following dangers according to internally approved calculation methods for preparations
	urmful
	prrosive
Su	allowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagi
	d stomach.
· Ca	arcinogenic categories
· IA	RC (International Agency for Research on Cancer)
No	one of the ingredients is listed.
$\cdot N'$	TP (National Toxicology Program)
No	one of the ingredients is listed.
· 09	SHA-Ca (Occupational Safety & Health Administration)
No	one of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 03/16/2022

CHEMICALS, INC.

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN3129
UN proper shipping name	
DOT IMDG, IATA	Water-reactive liquid, corrosive, n.o.s. WATER-REACTIVE LIQUID, CORROSIVE, N.O.S.
	WATER-REACTIVE EIQUID, CORROSIVE, N.O.S.
Transport hazard class(es)	
DOT	
· Class	4.3 Substances which, in contact with water, emit flammable gases
Label	4.3, 8
IMDG	
Class Label	<i>4.3 Substances which, in contact with water, emit flammable gases 4.3/8</i>
IATA	
Class	4.3 Substances which, in contact with water, emit flammable gases
Label	4.3 (8)
Packing group	
DOT, IMDG, IATA	Ι
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Substances which, in contact with water, emit flammal
	gases

Printing date 03/16/2022

CHEMICALS, INC

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

	(Contd. of page 8)
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· UN "Model Regulation":	UN 3129 WATER-REACTIVE LIQUID, CORROSIVE, N.O.S., 4.3 (8), I

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

109-99-9 Tetrahydrofuran [109-99-9]

97-94-9 triethylborane

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

109-99-9 Tetrahydrofuran [109-99-9] 22560-16-3 lithium triethylhydroborate

97-94-9 triethylborane

TLV (Threshold Limit Value established by ACGIH)

109-99-9 Tetrahydrofuran [109-99-9]

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 10)

SC

I (oral)

I (oral)

AЗ

US

Printing date 03/16/2022

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

	(Contd. of page 9)	
Hazard-de	termining components of labeling:	
	ofuran [109-99-9]	
	ethylhydroborate	
triethylbor		
Hazard sta		
H225	Highly flammable liquid and vapor.	
H250	<i>Catches fire spontaneously if exposed to air.</i>	
H260	In contact with water releases flammable gases, which may ignite spontaneously.	
H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H351	Suspected of causing cancer.	
H335-H33	6 May cause respiratory irritation. May cause drowsiness or dizziness.	
	nary statements	
	51+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.	
P305+P35	51+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor.	
P403+P23	•	
P411+P23		
P422	Store contents under inert gas.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	

· National regulations:

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Technical Department.

- Contact: Technical Director
- · Date of preparation / last revision 03/16/2022 / -
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Printing date 03/16/2022

Reviewed on 03/14/2022

Trade name: CALSELECTTM Lithium triethylborohydride, 1M in tetrahydrofuran

(Contd. of page 10)

US

BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Pyr. Liq. 1: Pyrophoric liquids – Category 1 Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

