

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

1 Identification

- **Product name**
- **Trade name:** Ethylenediamine, 99%
- **Item number:** 07-0570
- **CAS Number:**
107-15-3
- **EC number:**
203-793-3
- **Index number:**
612-006-00-6
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Strem Chemicals, Inc.
7 Mulliken Way
NEWBURYPORT, MA 01950
USA
info@strem.com
- **Information department:** Technical Department
- **Emergency telephone number:**
EMERGENCY: CHEMTREC: +1 (800) 424-9300
During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

ethylenediamine

· **Hazard statements**

H226 *Flammable liquid and vapor.*

H302+H312 *Harmful if swallowed or in contact with skin.*

H314 *Causes severe skin burns and eye damage.*

H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

H317 *May cause an allergic skin reaction.*

· **Precautionary statements**

P231 *Handle under inert gas.*

P284 *[In case of inadequate ventilation] wear respiratory protection.*

P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P422 *Store contents under inert gas.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

107-15-3 ethylenediamine

· **Identification number(s)**

· **EC number:** 203-793-3

(Contd. on page 3)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

· **Index number:** 612-006-00-6

(Contd. of page 2)

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:	0.88 ppm
· PAC-2:	9.7 ppm
· PAC-3:	20 ppm

7 Handling and storage

- **Handling:** Handle under inert gas.
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** Store contents under inert gas.
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
107-15-3 ethylenediamine	
PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Long-term value: 25 mg/m ³ , 10 ppm
TLV	Long-term value: 25 mg/m ³ , 10 ppm
	Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:** Wear protective clothing
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** A NIOSH approved respirator in accordance with 29 CFR 1910.134.

(Contd. on page 5)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Light yellow
· Odor:	Fish-like
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	8.5 °C (47 °F)
· Boiling point/Boiling range:	118 °C (244 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:** 385 °C (725 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Not determined.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· Lower:	2.7 Vol %
· Upper:	16.6 Vol %

· **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

· **Density at 20 °C (68 °F):** 0.899 g/cm³ (7.50216 lbs/gal)

· **Relative density** Not determined.

(Contd. on page 6)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 5)

- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water at 20 °C (68 °F):** 0.05 g/l
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic at 20 °C (68 °F):** 1.54 mPas
 - Kinematic:** Not determined.
 - Organic solvents:** 100.0 %
 - VOC content:** 100.0 %
- **Other information** 899.0 g/l / 7.50 lb/gl
No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

107-15-3 ethylenediamine

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	730 mg/kg (rabbit)
Inhalative	LC50/4 h	0.3 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** Caustic effect on skin and mucous membranes.
Irritant to skin and mucous membranes.
 - **on the eye:** Strong caustic effect.
- **Sensitization:**
 - Sensitization possible through inhalation.
 - Sensitization possible through skin contact.
- **Additional toxicological information:**
 - Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Substance is not listed.

(Contd. on page 7)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 6)

· **NTP (National Toxicology Program)**

Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1604
- **UN proper shipping name**
- **DOT** Ethylenediamine
- **IMDG, IATA** ETHYLENEDIAMINE

· **Transport hazard class(es)**

· **DOT**



- **Class** 8 Corrosive substances

(Contd. on page 8)



Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 7)

· Label	8, 3
· IMDG	
	
· Class	8 Corrosive substances
· Label	8/3
· IATA	
	
· Class	8 Corrosive substances
· Label	8 (3)
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	83
· Segregation groups	Alkalis
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG35 Stow "separated from" acids.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· Hazardous substance:	5000 lbs, 2270 kg
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1604 ETHYLENEDIAMINE, 8 (3), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara

· **Section 355 (extremely hazardous substances):**

Substance is listed.

(Contd. on page 9)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 8)

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

D

· **TLV (Threshold Limit Value established by ACGIH)**

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

ethylenediamine

· **Hazard statements**

H226 Flammable liquid and vapor.

H302+H312 Harmful if swallowed or in contact with skin.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

· **Precautionary statements**

P231 Handle under inert gas.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

(Contd. on page 10)

Safety Data Sheet
according to OSHA HCS

Printing date 07/18/2021

Reviewed on 07/18/2021

Trade name: Ethylenediamine, 99%

(Contd. of page 9)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Technical Department.

· **Contact:** Technical Director

· **Date of preparation / last revision** 07/18/2021 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1