

Printing date 15.07.2021 Revision: 14.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)
- · Item number: 11-1007
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Strem Chemicals, Inc.

7 Mulliken Way

NEWBURYPORT, MA 01950

USA

info@strem.com

- · Further information obtainable from: Technical Department
- · 1.4 Emergency telephone number:

EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS06 skull and crossbones

Acute Tox. 1 H330 Fatal if inhaled.



GHS08 health hazard

Carc. 1A H350 May cause cancer.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

(Contd. of page 1)

· Hazard pictograms









GHS02

02 GHS05

GHS06 GH

· Signal word Danger

· Hazard-determining components of labelling:

Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

· Hazard statements

H260 In contact with water releases flammable gases which may ignite spontaneously.

H330 Fatal if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P231+P232 Handle under inert gas. Protect from moisture.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description

Sodium oxide/sodium on alumina, Olefin Isomerization

Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

(Contd. of page 3)

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid
Colour: White

Odour: Odourless

Odour threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

(Contd. on page 5)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

	(Contd. of page
· Flash point:	Not applicable.
· Flammability (solid, gas):	Flammable. Contact with water liberates extremely flammable gases.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Not determined.
· Explosive properties:	Not determined.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not applicable.
 Density: Relative density Vapour density Evaporation rate 	Not determined. Not determined. Not applicable. Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
· Solvent content: Organic solvents: VOC (EC)	0.0 % 0.00 %
Solids content: · 9.2 Other information	100.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Contact with water releases flammable gases.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Fatal if inhaled.

(Contd. on page 6)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

(Contd. of page 5)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes severe skin burns and eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

May cause cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14:	Transport is	ıformat	ion
-------------	--------------	---------	-----

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN2813
- · 14.2 UN proper shipping name
- · ADR 2813 WATER-REACTIVE SOLID, N.O.S.

· IMDG, IATA WATER-REACTIVE SOLID, N.O.S.

(Contd. on page 7)



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR	
**	
· Class · Label	4 4.3
· IMDG, IATA	
· Class	4.3 Substances which, in contact with water, emit flammab gases.
· Label	4.3
· 14.4 Packing group · ADR, IMDG, IATA	I
· 14.5 Environmental hazards: · Marine pollutant:	No
 14.6 Special precautions for user EMS Number: Stowage Category Stowage Code Handling Code Segregation Code 	Not applicable. F-G,S-N E SW2 Clear of living quarters. H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 whe stowed on deck of a containership a minimum distance of tw container spaces athwartship shall be maintained, whe stowed on ro-ro ships a distance of 6 m athwartship shall b maintained.
· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	e x II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 2813 WATER-REACTIVE SOLID, N.O.S., 4.3, I



Printing date 15.07.2021 Revision: 14.07.2021

Trade name: Sodium oxide/sodium on alumina, Olefin Isomerization Catalyst (Na₂O 11.5-13.5%, Na 1.8-3.0%)

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category

H1 ACUTE TOXIC

- O2 Substances and mixtures which in contact with water emit flammable gases
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 20 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 40
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Carcinogenic hazardous material group I (extremely dangerous).

Carcinogenic hazardous material group II (very dangerous).

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department.
- · Contact: Technical Director
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases - Category 1

Acute Tox. 1: Acute toxicity – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Sens. 1: Skin sensitisation – Category I

Carc. 1A: Carcinogenicity - Category 1A

GB