

Printing date 07/20/2021 Reviewed on 07/15/2021

1 Identification

· Product name

· Trade name: Tri-i-butylaluminum, min. 95%

• *Item number:* 93-1358

• CAS Number: 100-99-2 • EC number: 202-906-3

• Index number: 013-004-00-2

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Strem Chemicals, Inc. 7 Mulliken Way NEWBURYPORT, MA 01950

USA

info@strem.com

· Information department: Technical Department

· Emergency telephone number:

EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Pyr. Liq. 1 H250 Catches fire spontaneously if exposed to air.

Water-react. 1 H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

- · Label elements
- · GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

triisobutylaluminium

· Hazard statements

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases, which may ignite spontaneously.

(Contd. on page 2)



Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

(Contd. of page 1)

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 4Reactivity = 2

The substance demonstrates unusual reactivity with water.

· HMIS-ratings (scale 0 - 4)

HEALTH 3 Health = 3FIRE 4 Fire = 4REACTIVITY 2 Reactivity = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

100-99-2 triisobutylaluminium

- · Identification number(s)
- · EC number: 202-906-3
- · Index number: 013-004-00-2

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

US



Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

44 mg/m3

· PAC-2:

290 mg/m3

· PAC-3:

1,800 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

(Contd. of page 3)



Safety Data Sheet according to OSHA HCS

Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

. .

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

100-99-2 triisobutylaluminium

REL Long-term value: 2 mg/m³

as Al

TLV Long-term value: 1* mg/m³ as Al;*as repirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment: Wear protective clothing
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment: A NIOSH approved respirator in accordance with 29 CFR 1910.134.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles



Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

(Contd. of page 4)

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color: Odor:	Colorless Odorless
· Oaor: · Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	4 °C (39 °F)
Boiling point/Boiling range:	73 °C (163 °F)
Flash point:	-22 °C (-8 °F)
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Spontaneously flammable in air.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	0.95 hPa (1 mm Hg)
Density at 20 °C (68 °F):	$0.781 \ g/cm^3 \ (6.51745 \ lbs/gal)$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)



Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

(Contd. of page 5)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- $\cdot \textbf{\textit{Aquatic toxicity:}} \ \textit{No further relevant information available}.$
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

US



Printing date 07/20/2021 Reviewed on 07/15/2021

 ${\it Trade\ name:\ Tri-i-butylaluminum,\ min.\ 95\%}$

(Contd. of page 6)

Transport information	
UN-Number DOT, IMDG, IATA	UN3394
UN proper shipping name DOT IMDG, IATA	Organometallic substance, liquid, pyrophoric, water-reactive ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC WATER- REACTIVE
Transport hazard class(es) DOT	
DNGEROUS THE	
Class Label	4.2 Substances liable to spontaneous combustion 4.2, 4.3
IMDG	
Class Label	4.2 Substances liable to spontaneous combustion 4.2/4.3
Class Label	4.2 Substances liable to spontaneous combustion 4.2 (4.3)
Packing group DOT, IMDG, IATA	I
Environmental hazards: Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category Handling Code Segregation Code	Not applicable. X333 F-G,S-M D H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 when stowed o deck of a containership a minimum distance of two container space athwartship shall be maintained, when stowed on ro-ro ships distance of 6 m athwartship shall be maintained. SG35 Stow "separated from" acids. SG63 Stow "separated longitudinally by an intervening complet compartment or hold from" Class 1.



Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

	(Contd. of page 7
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	On passenger aircraft/rail: Forbidden
· Quantity limitations	On cargo aircraft only: Forbidden
· IMDG	0
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE, 4.2 (4.3), I

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

(Contd. of page 8)



Safety Data Sheet according to OSHA HCS

Printing date 07/20/2021 Reviewed on 07/15/2021

Trade name: Tri-i-butylaluminum, min. 95%

· Hazard pictograms





GHS02

GHS05

- · **Signal word** Danger
- · Hazard-determining components of labeling:

triisobutylaluminium

· Hazard statements

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases, which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department.
- · Contact: Technical Director
- · Date of preparation / last revision 07/20/2021 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Pyr. Liq. 1: Pyrophoric liquids - Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases - Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B