

Printing date 21.07.2021 Revision: 15.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

· Item number: 98-4007

· CAS Number:

75-24-1

• **EC number:** 200-853-0

· Index number:

013-004-00-2

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Strem Chemicals, Inc.

7 Mulliken Way

NEWBURYPORT, MA 01950

USA

info@strem.com

· Further information obtainable from: Technical Department

· 1.4 Emergency telephone number:

EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Pyr. Liq. 1 H250 Catches fire spontaneously if exposed to air.

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS05

· Signal word Danger

(Contd. on page 2)



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

(Contd. of page 1)

· Hazard-determining components of labelling:

trimethylaluminium

· Hazard statements

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH014 Reacts violently with water.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description

75-24-1 trimethylaluminium

- · Identification number(s)
- EC number: 200-853-0
- · Index number: 013-004-00-2

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 \cdot 7.3 Specific end use(s) No further relevant information available.

GB -



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

75-24-1 trimethylaluminium

WEL Long-term value: 2 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Colourless
Odour: Odourless
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: 15.4 °C

(Contd. on page 5)



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

	(Contd. of pag
Initial boiling point and boiling range	e: 127 °C
· Flash point:	-17 °C
Flammability (solid, gas):	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Spontaneously flammable in air.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure at 20 °C:	9 hPa
Density at 20 °C:	0.752 g/cm^3
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC (EC)	0.00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 6)



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

(Contd. of page 5)

- · Serious eye damage/irritation
 - Causes severe skin burns and eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION	14: Tra	nsport	info	rmat	ion

· 14.1 UN-Number · ADR, IMDG, IATA	UN3394
· 14.2 UN proper shipping name · ADR · IMDG, IATA	3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER- REACTIVE ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER- REACTIVE

(Contd. on page 7)



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

	(Contd. of page
· 14.3 Transport hazard class(es)	
$\cdot ADR$	
4	
· Class	4
· Label	4.2+4.3
· IMDG	
4	
· Class	4.2 Substances liable to spontaneous combustion.
· Label	4.2/4.3
· IATA	
4	
Class	4.2 Substances liable to spontaneous combustion.
· Label	4.2 (4.3)
· 14.4 Packing group	
· ADR, IMDG, IATA	I
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· EMS Number:	F- G , S - M
· Stowage Category · Handling Code	D H1 Keep as dry as reasonably practicable
Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 whe
	stowed on deck of a containership a minimum distance of tw
	container spaces athwartship shall be maintained, whe
	stowed on ro-ro ships a distance of 6 m athwartship shall l
	maintained. SG35 Stow "separated from" acids.
	SG63 Stow "separated longitudinally by an intervening
	complete compartment or hold from" Class 1.
· 14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity (Contd. on page)



Printing date 21.07.2021 Revision: 15.07.2021

Trade name: Trimethylaluminum, elec. gr. (99.999+%-Al) PURATREM, 98-1955, contained in 50 ml electropolished Swagelok® cylinder (96-1077) for CVD/ALD

(Contd. of page 7)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER- REACTIVE, 4.2 (4.3), I

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category

P7 PYROPHORIC LIQUIDS AND SOLIDS

01 Substances or mixtures with hazard statement EUH014

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department.
- · Contact: Technical Director
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Pyr. Liq. 1: Pyrophoric liquids – Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

 $Skin\ Corr.\ 1B:\ Skin\ corrosion/irritation-Category\ 1B$

GB