

Printing date 07/17/2021

Reviewed on 07/14/2021

1 Identification

- **Product name**
- **Trade name:** *Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)*
- **Item number:** 28-1910
- **CAS Number:**
7440-02-0
- **EC number:**
231-111-4
- **Index number:**
028-002-00-7
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Strem Chemicals, Inc.
7 Mulliken Way
NEWBURYPORT, MA 01950
USA
info@strem.com
- **Information department:** Technical Department
- **Emergency telephone number:**
EMERGENCY: CHEMTREC: + 1 (800) 424-9300
During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Self-heat. 1 H251 Self-heating: may catch fire.



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

nickel
molybdenum

· **Hazard statements**

H251 Self-heating: may catch fire.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Substances**

· **CAS No. Description**

7440-02-0 nickel

· **Identification number(s)**

· **EC number:** 231-111-4

· **Index number:** 028-002-00-7

(Contd. on page 3)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 2)

· Dangerous components:

7439-98-7	molybdenum	1.0%
-----------	------------	------

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: If symptoms persist consult doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: No special measures required.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

7440-02-0	nickel	4.5 mg/m3
-----------	--------	-----------

7439-98-7	molybdenum	30 mg/m3
-----------	------------	----------

· PAC-2:

7440-02-0	nickel	50 mg/m3
-----------	--------	----------

7439-98-7	molybdenum	330 mg/m3
-----------	------------	-----------

(Contd. on page 4)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 3)

· PAC-3:		
7440-02-0	nickel	99 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
7440-02-0 nickel	
PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A
TLV	Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction
7439-98-7 molybdenum	
PEL	Long-term value: 15* mg/m ³ *Total dust
TLV	Long-term value: 10* 3** mg/m ³ as Mo; *inhalable fraction ** respirable fraction

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:** A NIOSH approved respirator in accordance with 29 CFR 1910.134.

(Contd. on page 5)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Powder
· Color:	Black
· Odor:	Odorless
· Odor threshold:	Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Flammable.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Not determined.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure:** Not applicable.

· **Density:** Not determined.

· **Relative density** Not determined.

(Contd. on page 6)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 5)

· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

2B

· **NTP (National Toxicology Program)**

R

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)




(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1378
· UN proper shipping name	
· DOT	Metal catalyst, wetted
· IMDG, IATA	METAL CATALYST, WETTED
· Transport hazard class(es)	
· DOT	
	
· Class	4.2 Substances liable to spontaneous combustion
· Label	4.2
· IMDG	
	
· Class	4
· Label	4.2
· IATA	
	
· Class	4.2 Substances liable to spontaneous combustion

(Contd. on page 8)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 7)

· Label	4.2
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· EMS Number:	F-H,S-M
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: 50 kg
· UN "Model Regulation":	UN 1378 METAL CATALYST, WETTED, 4.2, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· Section 355 (extremely hazardous substances):	Substance is not listed.	
· Section 313 (Specific toxic chemical listings):	7440-02-0	nickel
· TSCA (Toxic Substances Control Act):	Substance is listed.	
· Proposition 65		
· Chemicals known to cause cancer:	7440-02-0	nickel
· Chemicals known to cause reproductive toxicity for females:	Substance is not listed.	
· Chemicals known to cause reproductive toxicity for males:	Substance is not listed.	
· Chemicals known to cause developmental toxicity:	Substance is not listed.	
· Carcinogenic categories		
· EPA (Environmental Protection Agency)	Substance is not listed.	
· TLV (Threshold Limit Value established by ACGIH)	7440-02-0	nickel
	7439-98-7	molybdenum
		A5
		A3

(Contd. on page 9)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0 nickel

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

nickel

molybdenum

· **Hazard statements**

H251 Self-heating: may catch fire.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Technical Department.*

· **Contact:** *Technical Director*

· **Date of preparation / last revision** *07/17/2021 / -*

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Safety Data Sheet
according to OSHA HCS

Printing date 07/17/2021

Reviewed on 07/14/2021

Trade name: Nickel (skeletal), molybdenum promoted (1 wt%) (supplied under water) (Actimet® 8040P)

(Contd. of page 9)

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Self-heat. 1: Self-heating substances and mixtures – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

US