Printing date 07/21/2021

Reviewed on 07/21/2021

## **1** Identification

- · Product name
- · Trade name: Bismuth powder (99.999%)
- *Item number: 93-8348*
- CAS Number: 7440-69-9
- *EC number*:
- 231-177-4
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Strem Chemicals, Inc.
  7 Mulliken Way
- NEWBURYPORT, MA 01950 USA info@strem.com
- · Information department: Technical Department
- Emergency telephone number: EMERGENCY: CHEMTREC: + 1 (800) 424-9300 During normal opening times: +1 (978) 499-1600

## 2 Hazard(s) identification

Classification of the substance or mixture

Flam. Sol. 2 H228 Flammable solid.

- · Label elements
- · GHS label elements
- *The substance is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms*



· Signal word Warning

· Hazard statements

H228 Flammable solid.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P280 Wear protective gloves / eye protection / face protection.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- *P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 2)

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Bismuth powder (99.999%) (Contd. of page 1) · Classification system: · NFPA ratings (scale 0 - 4) Health = 4Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3 0 FIRE Fire = 0**REACTIVITY O** *Reactivity* = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- 7440-69-9 bismuth
- · Identification number(s)
- EC number: 231-177-4

#### 4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Generally the product does not irritate the skin.*
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: No special measures required.

(Contd. on page 3)

US -

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name:	Bismuth	powder	(99.999%)
-------------	---------	--------	-----------

	(Contd. of page 2)
• Methods and material for containment and cleaning up:	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
· PAC-1:	
	15 mg/m3
· PAC-2:	
	170 mg/m3
· PAC-3:	
	990 mg/m3

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

US

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Bismuth powder (99.999%)

(Contd. of page 3)

• *Material of gloves* The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

# 9 Physical and chemical properties

Information on basic physical and chemical properties         General Information         Appearance:         Form:       Powder         Color:       Grey         Odor threshold:       Not determined.         • pH-value:       Not applicable.         • Change in condition       Not applicable.         Melting point/Melting range:       271.3 °C (520 °F)         Boiling point/Melting range:       1.560 °C (35 °F)         • Flash point:       Not applicable.         • Flammability (solid, gaseous):       Flammable.         • Jgnition temperature:       Not determined.         Decomposition temperature:       Not determined.         • Danger of explosion:       Not determined.         • Auto igniting:       Not determined.         • Lower:       Not determined.         • Vapor pressure:       Not determined.         • Vapor density at 20 °C (68 °F):       9.8 g/cm³ (81.781 lbs/gal)         • Bulk density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not deplicable.         • Vapor density       Not deplicable. <th></th>	
· Appearance:PowderForm:PowderGolor:Grey· Odor:Odorless· Odor threshold:Not determined.· pH-value:Not applicable.· Change in condition Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)· Flash point:Not applicable.· Flash point:Not applicable.· Flash point:Not applicable.· Jenition temperature:Flammabile.· Decomposition temperature:Not determined.· Danger of explosion:Not determined.· Not giptiring:Not determined.· Supper:Not determined.· Vapper:Not determined.· Vapor pressure:Not applicable.· Vapor density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Sulk density at 20 °C (68 °F):6.000 kg/m³· Relative densityNot applicable.· Vapor densityNot applicable.	
Form:PowderColor:GreyOdorOdorlessOdor threshold:Not determined.• pH-value:Not applicable.• Change in condition Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)• Flash point:Not applicable.• Jgnition temperature:Not determined.Decomposition temperature:Not determined.• Danger of explosion:Not determined.• Lower: Upper:Not determined.• Vapor pressure:Not applicable.• Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)• Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.• Vapor density Vapor densityNot applicable.• Vapor density	
Color:Grey Odorless• Odor threshold:Not determined.• pH-value:Not applicable.• Change in condition Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)• Flash point:Not applicable.• Flash point:Not applicable.• Flammability (solid, gaseous):Flammable.• Ignition temperature:Not determined.• Decomposition temperature:Not determined.• Auto igniting:Not determined.• Auto igniting:Not determined.• Danger of explosion:Not determined.• Vapor pressure:Not applicable.• Vapor pressure:Not applicable.• Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)• Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.• Vapor densityNot applicable.• Density at 20 °C (68 °F):6.000 kg/m³ Not applicable.• Kelative densityNot applicable.• Vapor densityNot applicable.• Vapor densityNot applicable.• Kaporation rateNot applicable.	
· OdorOdorless Not determined.· Odor threshold:Not applicable.· pH-value:Not applicable.· Change in condition Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)· Flash point:Not applicable.· Flash point:Not applicable.· Flammability (solid, gaseous):Flammable.· Ignition temperature:Not determined.· Decomposition temperature:Not determined.· Auto igniting:Not determined.· Danger of explosion:Not determined.· Lower: Upper:Not determined.· Vapor pressure:Not applicable.· Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.· Vapor density · Vapor densityNot applicable.· Vapor density · Vapor densityNot applicable.	
· Odor threshold:Not determined.· pH-value:Not applicable.· Change in condition Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)· Flash point:Not applicable.· Flash point:Not applicable.· Flammability (solid, gaseous):Flammable.· Flammability (solid, gaseous):Flammable.· Decomposition temperature:Not determined.· Decomposition temperature:Not determined.· Danger of explosion:Not determined.· Durger of explosion:Not determined.· Durger:Not determined.· Durger:Not determined.· Durger:Not determined.· Durger:Not applicable.· Durger:Not determined.· Vapor pressure:Not applicable.· Bulk density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Bulk densityNot determined.· Vapor densityNot applicable.· Vapor densityNot applicable.· Not applicable.Not applicable.	
• Change in condition       271.3 °C (520 °F)         Boiling point/Boiling range:       1.560 °C (35 °F)         • Flash point:       Not applicable.         • Flammability (solid, gaseous):       Flammable.         • Ignition temperature:       Not determined.         • Decomposition temperature:       Not determined.         • Danger of explosion:       Not determined.         • Danger of explosion:       Not determined.         • Vapor pressure:       Not applicable.         • Vapor pressure:       Not applicable.         • Density at 20 °C (68 °F):       9.8 g/cm³ (81.781 lbs/gal)         • Bulk density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not determined.         • Vapor density       Not applicable.         • Density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not applicable.         • Vapor density       Not applicable.	
Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)Flash point:Not applicable.Flash point:Not applicable.Flammability (solid, gaseous):Flammable.Ignition temperature:Not determined.Decomposition temperature:Not determined.Oanger of explosion:Not determined.Explosion limits: Upper:Not determined.Vapor pressure:Not determined.Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.Vapor density Not applicable.Not applicable.Evaporation rateNot applicable.	
Melting point/Melting range:271.3 °C (520 °F) 1.560 °C (35 °F)Flash point:Not applicable.Flash point:Not applicable.Flammability (solid, gaseous):Flammable.Ignition temperature:Not determined.Decomposition temperature:Not determined.Oanger of explosion:Not determined.Explosion limits: Upper:Not determined.Vapor pressure:Not determined.Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.Vapor density Not applicable.Not applicable.Evaporation rateNot applicable.	
Boiling point/Boiling range:1.560 °C (35 °F)· Flash point:Not applicable.· Flammability (solid, gaseous):Flammable.· Ignition temperature:Not determined.Decomposition temperature:Not determined.· Auto igniting:Not determined.· Danger of explosion:Not determined.· Danger of explosion:Not determined.· Explosion limits:Not determined.· Lower:Not determined.· Upper:Not determined.· Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Bulk density at 20 °C (68 °F):6.000 kg/m³· Relative densityNot determined.· Vapor densityNot determined.· Vapor densityNot applicable.· Evaporation rateNot applicable.	
• Flammability (solid, gaseous):       Flammable.         • Ignition temperature:       Not determined.         • Decomposition temperature:       Not determined.         • Auto igniting:       Not determined.         • Danger of explosion:       Not determined.         • Danger of explosion:       Not determined.         • Dure:       Not determined.         • Upper:       Not determined.         • Vapor pressure:       Not applicable.         • Density at 20 °C (68 °F):       9.8 g/cm³ (81.781 lbs/gal)         • Bulk density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not determined.         • Vapor density       Not applicable.         • Density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not applicable.         • Vapor density       Not applicable.	
• Ignition temperature:       Not determined.         • Auto igniting:       Not determined.         • Auto igniting:       Not determined.         • Danger of explosion:       Not determined.         • Danger of explosion:       Not determined.         • Explosion limits:       Image: Not determined.         • Lower:       Not determined.         • Upper:       Not determined.         • Vapor pressure:       Not applicable.         • Density at 20 °C (68 °F):       9.8 g/cm³ (81.781 lbs/gal)         • Bulk density at 20 °C (68 °F):       6.000 kg/m³         • Relative density       Not determined.         • Vapor density       Not applicable.         • Not applicable.       Not applicable.	
Decomposition temperature:Not determined.Auto igniting:Not determined.Danger of explosion:Not determined.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapor pressure:Not applicable.Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)Bulk density at 20 °C (68 °F):6.000 kg/m³Relative densityNot determined.Vapor densityNot applicable.Evaporation rateNot applicable.	
• Auto igniting:Not determined.• Danger of explosion:Not determined.• Explosion limits: Lower: Upper:Not determined.• Vapor pressure:Not determined.• Vapor pressure:Not applicable.• Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)• Bulk density at 20 °C (68 °F):6.000 kg/m³ Not determined.• Vapor density · Vapor densityNot applicable.• Vapor density · Vapor densityNot applicable.	
Danger of explosion:Not determined.Explosion limits: Lower: Upper:Not determined.Vapor pressure:Not determined.Vapor pressure:Not applicable.Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)Bulk density at 20 °C (68 °F):6.000 kg/m³Relative density Vapor densityNot applicable.Vapor density Evaporation rateNot applicable.	
<ul> <li>Explosion limits:         <ul> <li>Lower:</li> <li>Not determined.</li> <li>Vpper:</li> <li>Not applicable.</li> </ul> </li> <li>Vapor pressure:</li> <li>Density at 20 °C (68 °F):</li> <li>9.8 g/cm<sup>3</sup> (81.781 lbs/gal)</li> <li>Bulk density at 20 °C (68 °F):</li> <li>6.000 kg/m<sup>3</sup></li> <li>Relative density</li> <li>Not determined.</li> <li>Vapor density</li> <li>Not applicable.</li> <li>Evaporation rate</li> <li>Not applicable.</li> </ul>	
Lower: Upper:Not determined.Vapor pressure:Not applicable.Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)Bulk density at 20 °C (68 °F):6.000 kg/m³Relative densityNot determined.Vapor densityNot applicable.Evapor ation rateNot applicable.	
Upper:Not determined.· Vapor pressure:Not applicable.· Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Bulk density at 20 °C (68 °F):6.000 kg/m³· Relative densityNot determined.· Vapor densityNot applicable.· Evaporation rateNot applicable.	
· Vapor pressure:Not applicable.· Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)· Bulk density at 20 °C (68 °F):6.000 kg/m³· Relative densityNot determined.· Vapor densityNot applicable.· Evaporation rateNot applicable.	
• Density at 20 °C (68 °F):9.8 g/cm³ (81.781 lbs/gal)• Bulk density at 20 °C (68 °F):6.000 kg/m³• Relative densityNot determined.• Vapor densityNot applicable.• Evaporation rateNot applicable.	
• Bulk density at 20 °C (68 °F):6.000 kg/m³• Relative densityNot determined.• Vapor densityNot applicable.• Evaporation rateNot applicable.	
Relative densityNot determined.Vapor densityNot applicable.Evaporation rateNot applicable.	
· Vapor densityNot applicable.· Evaporation rateNot applicable.	
• Evaporation rate Not applicable.	
· Solubility in / Miscibility with	
Water:   Insoluble.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic: Not applicable.	
Kinematic: Not applicable.	
• Solvent content: Organic solvents: 0.0 %	
5	
(Contd. on p	

Printing date 07/21/2021

CHEMICALS.

Reviewed on 07/21/2021

(Contd. of page 4)

Trade name: Bismuth powder (99.999%)

VOC	content:
100	comem.

0.0 g/l / 0.00 lb/gl

100.0 %

Solids content: · Other information

No further relevant information available.

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11** Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

7440-69-9 bismuth

Oral LD50 5000 mg/kg (rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

# **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

US

Printing date 07/21/2021

Reviewed on 07/21/2021

Trade name: Bismuth powder (99.999%)

· Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:


Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	UN3089
DOT, IMDG, IATA	0143069
UN proper shipping name DOT	Martal and the Clause all and a
IMDG, IATA	Metal powders, flammable, n.o.s. METAL POWDER, FLAMMABLE, N.O.S.
Transport hazard class(es)	METALI OWDER, I LAMMADEL, N.O.S.
•	
DOT	
<b>W</b>	
Class	4
Label	4.1
IMDG, IATA	
Class	4
Label	4.1
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Segregation groups	Heavy metals and their salts (including their organometal compounds), powdered metals
Stowage Category	A
Handling Code	H1 Keep as dry as reasonably practicable



(Contd. of page 5)



Printing date 07/21/2021

CHEMICALS, INC

Reviewed on 07/21/2021

Trade name: Bismuth powder (99.999%)

	(Contd. of page	
· Segregation Code	SG17 Stow "separated from" class 5.1 SG25 Stow "separated from" goods of classes 2.1 and 3. SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.	
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
· Transport/Additional information:		
· IMDG		
· Limited quantities (LQ)	5 kg	
$\cdot$ Excepted quantities (EQ)	Code: El	
· · · · · · · · · · · · · · · · · · ·	Maximum net quantity per inner packaging: 30 g	
	Maximum net quantity per outer packaging: 1000 g	
· UN ''Model Regulation'':	UN 3089 METAL POWDERS, FLAMMABLE, N.O.S., 4.1, III	

#### **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

Substance is not listed.

• TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 8)

US

Printing date 07/21/2021

CHEMICALS, INC

Reviewed on 07/21/2021

Trade name: Bismuth powder (99.999%)

(Contd. of page 7)

• Hazard p	ictograms
GHS02	
· Signal w	ord Warning
• Hazard s	tatements
H228 Fla	ummable solid.
· Precautio	onary statements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P403+P2	233 Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemica	l safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department.
- · Contact: Technical Director
- · Date of preparation / last revision 07/21/2021 / -
- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- *PBT: Persistent, Bioaccumulative and Toxic*
- *vPvB: very Persistent and very Bioaccumulative*
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Sol. 2: Flammable solids Category 2